



## Stoßverbinder ohne Isolation nach DIN 46341

Ausführung in SE-Cu

galvanisch verzinkt

Temperaturbeständig bis +125°C

\* = nicht genormt nach DIN

Artikelnummer	Leiterquerschnitt Abmessungen in mm				
	in mm <sup>2</sup>	S	d1	L	
EHQ 560	- 0,5	0,10-0,50	0,4	1,2	12
EHQ 453	- 1	0,25-1,50	0,8	1,6	15
EHQ 454	- 2,5	>1,0-2,5	0,8	2,3	15
EHQ 455	- 6	>2,5-6,0	1,0	3,6	15
EHQ 460	- 10	>6,0-10,0	1,1	4,5	20
EHQ 461	- 16	>10,0-16,0	1,2	5,8	23
EHQ 486	- 25	>16,0-25,0	1,5	7,5	25
EHQ 487	- 35	>25,0-35,0	1,6	9,0	27
EHQ 480	- 50	>35,0-50,0	1,8	11,0	38
EHQ 481	- 70	>50,0-70,0	2,0	13,0	42
EHQ 482	- 95	>70,0-95,0	2,5	15,0	48
EHQ 519	- 120	>95,0-120,0	3,0	16,5	52
EHQ 520	- 150	>120,0-150,0	3,2	19,0	56
EHQ 537	- 185	>150,0-185,0 Sonderausführung	3,5	21,0	56



**Albert  
Schäfer  
Nachf.**

Albert Schäfer Nachf. GmbH  
Forststraße 154  
70193 Stuttgart

Telefon: 0711 633037-0  
Telefax: 0711 633037-29  
eMail: verkauf@albert-schaefer.de