



Rohrkabelschuhe

Ausführung in Kupfer

galvanisch verzinkt

Artikelnummer		Leiterquerschnitt in mm ²	Abmessung in mm		
			D	B	L
ASR	1,5-4	1,5	4,3	8,0	17,0
ASR	1,5-5	1,5	5,3	8,0	17,0
ASR	2,5-4	2,5	4,3	8,0	18,0
ASR	2,5-6	2,5	5,3	8,0	20,0
ASR	2,5-6	2,5	6,4	9,0	20,0
ASR	6-4	6,0	4,3	10,0	23,0
ASR	6-5	6,0	5,3	10,0	26,0
ASR	6-6	6,0	6,4	10,0	26,0
ASR	6-8	6,0	8,4	12,0	27,5
ASR	6-10	6,0	10,5	16,0	34,0
ASR	10-5	10,0	5,3	12,0	26,5
ASR	10-6	10,0	6,4	12,0	26,5
ASR	10-8	10,0	8,4	12,0	26,5
ASR	10-10	10,0	10,5	18,0	35,5
ASR	10-12	10,0	13,0	18,5	39,5
ASR	16-4	16,0	4,3	12,4	31,0
ASR	16-5	16,0	5,3	12,4	31,0
ASR	16-6	16,0	6,4	12,4	31,0
ASR	16-8	16,0	8,4	12,4	31,0
ASR	16-10	16,0	10,5	15,0	33,0
ASR	16-12	16,0	13,0	20,0	42,5
ASR	25-5	25,0	5,3	14,0	32,0
ASR	25-6	25,0	6,4	14,0	32,0
ASR	25-8	25,0	8,4	18,0	34,0
ASR	25-10	25,0	10,5	18,0	34,0
ASR	25-12	25,0	13,0	20,0	45,0
ASR	35-6	35,0	6,4	16,0	38,0
ASR	35-8	35,0	8,4	16,0	38,0
ASR	35-10	35,0	10,5	17,5	40,5
ASR	35-12	35,0	13,0	18,0	47,5
ASR	50-6	50,0	6,4	18,0	43,0
ASR	50-8	50,0	8,4	18,0	43,0
ASR	50-10	50,0	10,5	18,0	43,0
ASR	50-12	50,0	13,0	18,0	51,5
ASR	50-14	50,0	15,0	25,0	55,5
ASR	50-16	50,0	17,0	26,0	59,5



**Albert
Schäfer
Nachf.**

Albert Schäfer Nachf. GmbH
Forststraße 154
70193 Stuttgart

Telefon: 0711 633037-0
Telefax: 0711 633037-29
eMail: verkauf@albert-schaefer.de



Artikelnummer		Leiterquerschnitt in mm ²	Abmessung in mm		
			D	B	L
ASR	70-6	70,0	6,4	21,8	50,0
ASR	70-8	70,0	8,4	21,8	50,0
ASR	70-10	70,0	10,5	21,8	50,0
ASR	70-12	70,0	13,0	21,8	50,0
ASR	70-14	70,0	15,0	21,8	59,0
ASR	70-16	70,0	17,0	26,0	63,0
ASR	95-5	95,0	5,3	25,0	57,0
ASR	95-6	95,0	6,4	25,0	57,0
ASR	95-8	95,0	8,4	25,0	57,0
ASR	95-10	95,0	10,5	25,0	57,0
ASR	95-12	95,0	13,0	25,0	57,0
ASR	95-14	95,0	15,0	25,0	65,5
ASR	95-16	95,0	17,0	27,0	69,5
ASR	95-20	95,0	21,0	29,5	77,5
ASR	120-8	120,0	8,4	28,0	60,0
ASR	120-10	120,0	10,5	28,0	60,0
ASR	120-12	120,0	13,0	28,0	60,0
ASR	120-14	120,0	15,0	28,0	66,0
ASR	120-16	120,0	17,0	28,0	66,0
ASR	150-10	150,0	10,5	30,5	69,0
ASR	150-12	150,0	13,0	30,5	69,0
ASR	150-14	150,0	15,0	30,5	69,0
ASR	150-20	150,0	21,0	30,5	69,0
ASR	185-10	185,0	10,5	34,0	69,0
ASR	185-12	185,0	13,0	34,0	79,0
ASR	185-14	185,0	15,0	34,0	79,0
ASR	185-16	185,0	17,0	34,0	79,0
ASR	185-20	185,0	21,0	34,0	79,0
ASR	240-10	240,0	10,5	38,0	93,0
ASR	240-12	240,0	13,0	38,0	93,0
ASR	240-14	240,0	15,0	38,0	93,0
ASR	240-16	240,0	17,0	38,0	93,0
ASR	240-18	240,0	19,0	38,0	93,0
ASR	240-20	240,0	21,0	38,0	93,0
ASR	300-12	300,0	13,0	13,0	100,0
ASR	300-14	300,0	15,0	15,0	100,0
ASR	300-16	300,0	17,0	17,0	100,0
ASR	300-18	300,0	19,0	19,0	100,0
ASR	300-20	300,0	21,0	21,0	100,0



**Albert
Schäfer
Nachf.**

Albert Schäfer Nachf. GmbH
Forststraße 154
70193 Stuttgart

Telefon: 0711 633037-0
Telefax: 0711 633037-29
eMail: verkauf@albert-schaefer.de



Artikelnummer		Leiterquerschnitt in mm ²	Abmessung in mm		
			D	B	L
ASR	500-16	500,0	17,0	56,0	126,0
ASR	500-18	500,0	19,0	56,0	126,0
ASR	500-20	500,0	21,0	56,0	126,0
ASR	630-18	630,0	19,0	65,0	140,0
ASR	630-20	630,0	21,0	65,0	140,0
ASR	800	800,0		73,5	170,0
ASR	1000	1000,0		81,0	200,0



**Albert
Schäfer
Nachf.**

Albert Schäfer Nachf. GmbH
Forststraße 154
70193 Stuttgart

Telefon: 0711 633037-0
Telefax: 0711 633037-29
eMail: verkauf@albert-schaefer.de